

# RISH FLEX 6005A



**Input: single-phase: 115 - 230 Vac**  
**Output: 5 Vdc 60 °C**  
**Efficiency up to 82%**  
**Strong overload without switch-off**  
**Flexible Power continuity : up to 35 W**  
**DIN Rail Mountable**  
**Extremely small size**  
**3 Year warranty**

## Features

### Input Data

Nominal Input Voltage (2 x Vac)	<b>115 – 230 Vac</b>
Input Voltage range (Vac)	<b>90 – 280</b>
Inrush Current (Vn and In Load) I <sup>2</sup> t	<b>≤ 7 A ≤ 5 msec.</b>
Frequency	<b>47 – 63 Hz ±6%</b>
Input Current (115 – 230 Vac)	<b>0.5 – 0.25 A</b>
Internal Fuse	<b>T 4 A</b>
External Fuse (recommended)	<b>6 A (MCB curve B)</b>

### Output Data

Output Voltage (Vn) Factory Setting ±3%	<b>5 Vdc</b>
Adjustment range (Vadj)	<b>4.75 – 5.25 Vdc</b>
Start up with Strong Load (capacitive load)	<b>≤ 50,000µF</b>
Turn-On delay after applying mains voltage	<b>1.5 sec. (max)</b>
Continuous Current at 5 V up to 40°C (In)	<b>5 A</b>
Continuous Current at 5 V up to 50°C (In)	<b>5 A</b>
Continuous Current at 5 V up to 60°C (In)	<b>5 A</b>
Power Boost Current at 5 Vdc up to 50°C(In)	<b>7 A ≤ 3 min.</b>
Current max. Overload ≅ 2Vdc (permanent)	<b>I<sub>max</sub>=I<sub>n</sub>50°Cx(1.3-1.4)</b>
Max current Short Circuit (I <sub>cc</sub> )	<b>10 A</b>
Hold-up Time ( min. Vac)	<b>Typ. 20 msec</b>
Residual Ripple	<b>≤ 80 mV<sub>pp</sub></b>
Efficiency	<b>≥ 82 %</b>
Over temperature Protection	<b>Yes. Shut-down output and automatic restart.</b>
Short-circuit protection	<b>Yes, Continuous Mode</b>
Dissipation power load max (W)	<b>6</b>
Over Load protection	<b>Yes, Continuous Mode</b>
Over Voltage Output protection	<b>Yes (typ. 15 Vdc)</b>
Parallel connection	<b>Yes</b>

### Climatic Data

Ambient Temperature operation	<b>-25°C up to +70 °C</b> <b>(&gt;60°C Derating 2.5% °C)</b>
Ambient Temperature Storage	<b>-40°C up to +85°C</b>
Humidity at 25 °C, no condensation	<b>95 % to 25°C</b>

### General Data

Isolation Voltage (In / Out)	<b>3000 Vac</b>
Isolation Voltage (In / PE)	<b>1605 Vac</b>
Isolation Voltage (Out / PE)	<b>500 Vac</b>
Protection Class (EN/IEC 60529)	<b>IP 20</b>
Reliability: MTBF IEC 61709	<b>&gt; 5,00,000 h</b>
Pollution Degree Environment	<b>2</b>
Connection Terminal Blocks Screw Type	<b>2.5 mm<sup>2</sup> (24 – 14 AWG)</b>
Protection class	<b>I with PE connected</b>
Dimension (w-h-d)	<b>50x120x50 mm</b>
Weight	<b>0.3 kg approx.</b>

## Norms and certifications

The CE mark in According to EMC 2004/108/EC and Low voltage directive 2006/95/EC.

### Electrical Safety

According to IEC/EN 60950 (VDE 0805) e EN 50178 (VDE 0160) for assembling device. The unit must be installed according to IEC/EN 60950. Input / Output separation: SELV EN60950-1 6 Edition, and PELV EN 60204-1. Double or reinforced insulation.

### EMC Immunity

EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN61000-6-2

### EMC Emission:

EN61000-6-4, EN61000-3-2

### Standards Conformity

EN 60204-1 Safety of Electrical Equipment Machines

