



Data Sheet

RISH CON SI-102



Measure



Control



Record



Analyze



Optimize

Application

The purpose of the RISH CON SI-102 is to electrically isolate input, outputs and power supply. The isolator fulfills all requirements and regulation concerning electromagnetic compatibility EMC and safety (IEC61326-1 and IEC 61010-1:2010).

The device has one input and provides two independent outputs in an extremely small space.

Product Features

Electric Isolation

- Two electrically isolated analog outputs prevent interference voltage and current. Solves grounding problem in meshed signal networks.
- High electric isolation between input and outputs – 2.3 kV, and power supply versus all other circuits – 3.0 kV.

Function

Simple dc isolator serves to electrically isolate input dc signal in the range 0 – 20 mA or 4-20 mA or 0-10V or 2-10V is then converted to signal 0 – 20 mA or 4-20 mA or 0-10V or 2-10V.

Features

- Electric isolation between input, outputs and power supply. Prevents false measurement due to spurious potentials.
- Processes live zero signals, provision for signal conversion. Green LED signals indicates device in operating condition.
- Electrical insulation between power supply versus all other circuits
- 3.0 kV, and between input and outputs -2.3 kV.

Technical Specifications

Measuring inputs

DC current standard ranges	<ul style="list-style-type: none"> • 0...20mA • 4...20mA • 1...5mA
Input resistance	≤ 15.5Ω
DC voltage standard ranges	<ul style="list-style-type: none"> • 0...10V • 2...10V • 1...5V
Input resistance	≥ 100 kΩ

Measuring output1 and output2

DC current standard ranges	<ul style="list-style-type: none"> • 0...20mA • 4...20mA
Burden voltage	<13V
External Resistance	$R_{ext\ max.} [k\Omega] = 12V / I_{AN} [mA]$ I_{AN} =Output circuit full scale value
DC voltage standard ranges	<ul style="list-style-type: none"> • 0...10V • 2...10V
Burden	$R_{ext\ min.} [k\Omega] = U_{AN} [V] / 5\ mA$ U_{AN} =Output circuit full scale value

Current limiter at $R_{ext} = 0$	< 42mA for voltage output
Voltage limiter at $R_{ext} = \infty$	< 20 V for current output
Residual ripple in Output	< 0.4% p.p.
Response time	< 50 ms
Common mode voltage	100V
Pollution degree	2

Power supply

Rated operating voltage	60...230...300V DC/AC OR 20...30...40V AC / 20...30...60V DC
Rated operating frequency	40 ... 50-60 ... 400 Hz
Power input	< 2W resp < 4 VA

Accuracy data (Acc to IEC 60688)

Basic Accuracy	Limit error < ± 0.2 % including linearity and reproducibility errors.
----------------	---

Reference conditions

Ambient temperature	23°C ± 2°C
Output burden	Current: 0.5 * R_{ext} max. Voltage: 2 * R_{ext} min.
Nominal value of Aux supply voltage	230V 50Hz or 60 Hz AC/DC 30V 50Hz or 60 Hz AC/DC

Influence factors

Temperature	± 0.01% per °C
Burden influence	< ± 0.1 % for current output < ± 0.1 % for voltage output
Switch-on drift	< ± 0.2%
Longtime drift	< ± 0.3% / 12 months
Magnetic field	< ±0.2 % (400 A/T)

Regulations

Electromagnetic Compatibility Protection	Acc. to IEC 61326 - 1 For Housing : IP40 Terminals : IP20
Electrical standards	Acc. to IEC 61010 -1 / EN 61 010 -1
Pollution degree	2
Over voltage category	III for power supply II for measuring input and measuring output
Test Voltage	Power supply versus : <ul style="list-style-type: none"> • All 3 kV, 50 Hz 1 min Measuring inputs versus : <ul style="list-style-type: none"> • Measuring outputs 2.3 kV, 50 Hz 1min & O/P1 to O/P 2: 500 V ,50 Hz , 1 min

Environmental condition

Climatic rating	Climate class 3 acc. to VDI /VDE 3540
Nominal Range of Use	0 °C to 45 °C (Usage group II)
Operating Temperature	-10 °C to 55 °C
Storage temperature	-40 °C to 70 °C
Annual mean relative humidity	< 75% standard Climatic rating.



Measure



Control



Record



Analyze



Optimize

Installation Data


Mechanical Housing	Lexan 940 (polycarbonate) Flammability Class V-0 acc. non dripping, free of halogen.
Mounting position	Rail mounting / wall mounting
Weight	Approx. 0.2kg

Connection Terminal

Connection Element	Conventional Screw type terminal with indirect wire pressure
Permissible cross section of the connection lead	4.0mm ² single wire or 2 x 2.5mm ² Fine wire
Permissible Vibrations Shocks	2 g acc. to EN 60 068-2-6 3 x 50 g 2 shocks each in 6 directions Acc. to EN 60 068-2-27


Connection	Terminal details	
Measuring input	+	3
	-	4
Measuring output 1	+	5
	-	6
Measuring output 2	+	7
	-	8
Auxiliary Supply	~ , +	1
	~ , -	2

Dimensions



Note : All Dimensions are in mm

Output characteristics



Electrical Connections



Measure



Control



Record



Analyze



Optimize

Ordering Information

Product Code	SI02-	XX	XX	XX	X	00000000
Input Range	0-20mA	32				
	1-5mA	53				
	4-20mA	55				
	0-10V	5H				
	2-10V	3C				
	1-5V	3B				
	0-75mV	3D				
	0-5V	3E				
	250V*	3G				
	0-60mV	3F				
	0-100mV	3H				
	0-15V*	5J				
	0-125V*	5K				
	0-75V*	5L				
	0-3V	5M				
	0-100V*	5N				
	0-50V	5P				
	0-310V*	5Q				
	0-30V*	5R				
	0-300V	5S				
	0-150V	5T				
	0-20V	5U				
	0-220V*	5V				
175V*	5W					
0-1V	5A					
Output Range1	0-20mA		32			
	4-20mA		55			
	0-10V		5H			
	2-10V		3C			
Output Range2	0-20mA			32		
	4-20mA			55		
	0-10V			5H		
	2-10V			3C		
Power Supply	24-60V AC/DC				F	
	60-300V AC/DC				H	

*Non standard Inputs

Ordering Example

SI02-555555H000000 – Rish CON SI 102, Input: 4-20mA, Output 1 : 4-20mA, Output 2 : 4-20mA, Aux 60-300 VAC/DC



Measure



Control



Record



Analyze



Optimize



RISHABH



Measure



Control



Record



Analyze



Optimize

RISHABH INSTRUMENTS LIMITED

Domestic (India): +91 253 2202099 | marketing@rishabh.co.in
International: +91 253 2202004/06/08/99 | global@rishabh.co.in
www.rishabh.co.in